

Technical Data Sheet


Shadow Ridge™ Shingle (Hip and Ridge Accessory)




PRODUCT DESCRIPTION

A shingle of three-piece construction (English-size) or four-piece construction (Metric-size; West Coast only) that combines durability with flexibility and good looks. Available in "English" dimensions – 12" x 36" overall, yielding three 12" x 12" caps, or "Metric" dimensions – 13-1/4" x 39-3/8" overall, yielding four 13-1/4" x 9-27/32" caps. Availability depends on sales region.

ENGLISH



METRIC



Colors: Shadow Ridge shingles are available in various colors. Color and product availability can vary by region; please check your region's product catalogue.

Limitations: Use on hips & ridges of roofs only after application of primary roofing shingles to both intersecting roof decks. These shingles are designed to be used with CertainTeed's shingles that reference the use of "Shadow Ridge" shingles. Use "Shadow Ridge" product colors that complement the shingle colors applied to the main roof. Special hand-sealed application is required for Miami-Dade acceptance. Contact CertainTeed's Technical Service Department @ 1-800-345-1145 for details.

Product Composition: Shadow Ridge shingles are composed of a fiber glass mat base. Ceramic coated mineral granules are tightly embedded in specially refined, water-resistant asphalt. The "English" version is a three-piece shingle that must be separated into individual pieces, each 12" x 12", by folding along the perforated lines. The "Metric" version is a four-piece shingle that must be separated into individual pieces, each 13-1/4" x 9-27/32", by folding along the perforated lines.

Applicable Standards:

ASTM D 3018, Type I

ASTM D 3462

ASTM E 108 Fire Resistance: Class A

ASTM D 3161, Type I Wind Resistance

ASTM D 3161, Class F* Wind Resistance

ICC-ES ESR-1389

Miami-Dade Product Control Approved*

UL 790 Fire Resistance: Class A

UL 997 Wind Resistance

NYC-MEA-120-79-M

*Special hand-sealed application required (Contact CertainTeed's Technical Service Department @ 1-800-345-1145 for details).

TECHNICAL DATA

	English	Metric
Weight/Bundle (approx.):	65 lb	80 lb
Dimensions (overall):	12" x 36"	13-1/4" x 39-3/8"
Separated into individual pieces:	12" x 12"	13-1/4" x 9-27/32"
Weather Exposure:	5"	5-5/8"
Coverage/bundle:	30 lin. ft.	45 lin. ft.

INSTALLATION

Each bundle of Shadow Ridge shingles has detailed installation instructions including diagrams.

Double-coursing will accent the rooflines and improve overall appearance.

AVAILABILITY AND COST

Availability: For the names of local distributors and dealers, please write Architectural Support, P.O. Box 860, Valley Forge, PA 19482; or call (800) 233-8990.

Cost: Contact a local distributor or dealer for current price information.

MAINTENANCE

Shadow Ridge shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

WARRANTY

This product has a limited warranty against manufacturing defects concurrent with the warranty of the field shingle with which it is installed.

TECHNICAL SERVICE

Complete technical support and assistance is available through CertainTeed's Technical Service Department @ 1-800-345-1145, Territory Managers, and the fully staffed and equipped Research and Development facility in Blue Bell, PA.

FOR MORE INFORMATION

Sales Support Group: 800-233-8990

Web site: www.certainteed.com

See us in Sweets printed and electronic publications

CertainTeed Roofing
P.O. Box 860
Valley Forge, PA 19482

© Copyright CertainTeed Corporation, 2009.
All rights reserved. Updated: 12/2009

CertainTeed 
Quality made certain. Satisfaction guaranteed.™