


## SwiftStart® Starter Shingles

### PRODUCT DESCRIPTION

SwiftStart® combines durability, flexibility and sealant adhesive for better resistance to potential blow-off and uplift. Its overall size of 15-1/4" x 38-3/4" yields two 7-5/8" x 38-3/4" starter pieces per shingle. Availability depends on sales region.



**Limitations:** Use as a starter course on shingle roofs with slopes greater than 2" per foot and having an exposure of  $\leq 5\text{-}5/8"$ . Apply SwiftStart in accordance with local building code requirements and following good roofing practice. Low slope application (2" - 4" per foot) requires additional underlayment. In areas where icing along eaves can cause a backup of water, apply CertainTeed WinterGuard® Waterproofing Shingle Underlayment, or its equivalent, to the deck according to application instructions provided with the product and on shingle package.

**Composition and Materials:** SwiftStart shingles are composed of a fiber glass mat base. Ceramic coated mineral granules are tightly embedded in specially refined, water-resistant asphalt. It is a two-piece shingle that must be separated into individual pieces, each 7-5/8" x 38-3/4", by folding along the perforated lines.

### Applicable Standards:

ASTM D3462  
ASTM D3018 Type I  
ICC-ES ESR-1389 and ESR-3537  
Miami-Dade County Product Control Approved  
Meets TDI Windstorm Requirements

ASTM D3161 Class F Wind Resistance  
ASTM E108 Class A Fire Resistance  
UL 790 Class A Fire Resistance  
Florida Product Approval #FL5444

### TECHNICAL DATA

Weight/Bundle (approx.):	62 lb
Dimensions (overall):	15-1/4" x 38-3/4"
Separates into individual pieces:	7-5/8" x 38-3/4"
Coverage/bundle:	116-1/4 lin. ft

### INSTALLATION

Each bundle of SwiftStart shingles has detailed installation instructions including diagrams and must be followed.

### MAINTENANCE

These shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

### WARRANTY

SwiftStart starter shingles have a limited warranty against manufacturing defects concurrent with the warranty of the field shingle with which it is installed. See CertainTeed's Asphalt Shingle Products Limited Warranty for specific details.

### TECHNICAL SUPPORT

Technical Service Department: 1-800-345-1145

e-mail: [RPG.T.Services@saint-gobain.com](mailto:RPG.T.Services@saint-gobain.com)

### FOR MORE INFORMATION

Customer Experience Team: 800-233-8990

e-mail: [gethelp@saint-gobain.com](mailto:gethelp@saint-gobain.com)

Web site: [www.certainteed.com](http://www.certainteed.com)

See us at our on-line specification writing tool, CertaSpec, at [www.certainteed.com/certaspec](http://www.certainteed.com/certaspec)

